



The ADA is an IP65 decorative and robust wall mounted amenity luminaire with a clear lens and black powder coat finish.

- A range of lumen outputs from 243-2121lm
- Colour Temperature: 3000k- 4000k
- Beam Angles: 15°, 25°, 30° or 40° (15D/25D/30D/40D)
- Lens: Clear glass lens
- Colour Options: White, Grey or Black (WH/GR/BK)
- Standard Non Dimming (/STD)
- Emergency, contact MID Technical for more details
- Distribution: Direct or Direct/Indirect (/DL/UDL)
- Mountings: Wall mounted
- IP Rating: IP65
- Polyester powder coating with treatment for outdoor
- Housing: Die cast aluminium
- Dimensions: (Diameter x Height)
 - /5.5W - Ø70 x 220mm
 - /15W - Ø110 x 400mm
 - /20W - Ø150 x 500mm

Exterior

| | | | |
|---|-----------------------------------|-------------------|--|
| Product | MI/ADA Wall IP65 LED Luminaire | | |
| Light Source | LED | | |
| System Power Luminaire lumens (4000K) | /5.5W 243lm | /15W 1628lm | |
| Size | Ø70 x 220mm | Ø110 x 400mm | |
| Beam Angle | /15D 15 Degree | /25D 25 Degree | /40D 40Degree |
| Driver | /STD Non Dimming | | |
| Colour Temperature | /830 4000k | | /840 4000k |
| Colour | /WH White | /GR Grey | /BK Black |
| Distribution | /DL Direct (Downlight) | | /UDL Direct/Indirect (Up/Downlight) |
| To Specify: ADA LED, 5.5W, 243lm, 4000k, LED wall mounted luminaire finished black supplied with standard integral control gear and 30 degree beam angle. Part code: MI/ADA/5.5W/243lm/STD/840/BK/30D | | | |

