

Recessed



A high quality recessed extruded system ideally suited for modular or continuous runs.

- Colour Temperatures: 3000k - 4000k - 6000k
 - White RAL9016, Black 9005 and Silver 9006 as standard, other RAL colours available
 - Available with Dimming (/STD/DALI/SDIM)
 - Wireless Control (/WI)
 - Available in Emergency (/ME3/ME3-ST/ME3-PRO)
 - Wireless Emergency (/ME3-WI)
 - Diffusers: Polar White or Micro Prismatic Optic (/PW/MPO)
 - Body: Aluminium Extrusion
 - Body Options: Trimmed /Plaster-in (/T/P)
 - Depth: 80mm
 - Available in continuous runs with aluminium infills.
- Please contact our technical department for further details

Product	MIR/ALU50 Recessed LED Linear			
Light Source	LED			
System Power <small>Luminaire lumens (4000K)</small>	/19W 2081lm	/31W 3330lm	/24W 2605lm	/39W 4169lm
Size	/12 1200 x 60mm		/15 1500 x 60mm	
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/WI Wireless Control
Colour Temperature	/830 3000k	/840 4000k	/860 6000k	
Colour	/WH White - RAL9016	/BK Black - RAL9005	/SLV Silver - RAL9006	
Diffuser Options	/PW Polar White Diffuser		/MPO Micro Prismatic Optic	
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency
To Specify: ALULINE 50 LED, trimmed, 24W, 4000k, 2605lm LED linear recessed finished white and is 1200mm long supplied complete with DALI control gear and polar white diffuser. Part code: MIR/ALU50/T/24W/2605lm/12/DALI/840/WH/PW				

