



The BOLLOVARD is an IP65 decorative bollard with a clear inner lens and no upright cut off. The bollard has an internal ballast tray for ease of maintenance.

- A lumen output of 674lm
- Colour Temperature: 4000k
- Beam Angle: 180 Degree Shield (/180DS)
- Lens: Clear polycarbonate vandal-resistant
- Colour: Black as standard (/BK)
- Standard Non Dimming (/STD)
- Available in Emergency (/ME3/ME3-ST/ME3-PRO)
- Mount kit with 200mm anchor bolts (included).
- Mountings: Root or Flange mounted (/RT/FL)
(Flange is required for Root Mounting option)
- Sensor: Microwave Sensor (/MW)
- IP Rating: IP65
- Flat top, black powder coat finish over chromate conversion coating (/BK)
- Housinh: Extruded aluminium body
- Dimensions: (Diameter x Height) Ø120 x 1019mm

Exterior

Product	MI/BOLV Bollard IP65 LED Luminaire		
Light Source	LED		
System Power <small>Luminaire lumens (4000K)</small>	/18.9W 674lm		
Size	Ø120 x 1019mm		
Driver	/STD Non Dimming		
Colour Temperature	/840 4000k		
Colour	/BK Black		
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: BOLV LED, 18.9W, 674lm, 5000k, LED bollard anchor root mounted luminaire finished black supplied with standard integral control gear. Part code: MI/BOLV/18.9W/674lm/STD/840/BK/RT			

Full 360 Degree Distribution As Standard

