



Root and Flange Options

**The BOSTON is an IP65 decorative and robust bollard with a clear lens and aluminium cone reflector. The bollard has an internal ballast tray for ease of maintenance.**

- A lumen output of 1566lm
- Colour Temperature: 4000k
- Lens: Clear polycarbonate vandal-resistant lens, aluminium cone reflector
- Colour: Black as standard (/BK)
- Available with dimming (/STD/DIM)
- Available in Emergency (/ME3/ME3-ST/ME3-PRO)
- Mounting: Root or Flange mounted (/RT/FL)
- Sensor: Microwave Sensor (/MW)
- IP Rating: IP65
- Domed top, black powder coat finish over chromate conversion coating
- Housing: Die cast aluminium body
- Dimensions: (Diameter x Height) Ø178 x 1073mm

Exterior

Product	MI/BOSTON Bollard IP65 LED Luminaire		
Light Source	LED		
System Power <small>Luminaire lumens (5000K)</small>	/17W 1566lm		
Size	Ø178 x 1073mm		
Driver	/STD Non Dimming	/DIM Dimming	
Colour Temperature	/840 4000k		
Colour	/BK Black		
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: BOSTON LED, 17W, 1566lm, 4000k, LED bollard anchor root mounted luminaire finished black supplied with standard integral control gear. Part code: MI/BOSTON/17W/1566lm/STD/840/BK/RT			

