BULLET-SQ-WW DOWNLIGHT





- A low glare architectural wall washer with a square minimal bezel. Fitted with integral IP44 protective lens and a deep matt black baffle to minimise glare.

- Available in 8 & 14 watts

- 508/767lumens

- IP44 as standard

- Available with Dimming (/STD/DALI/SDIM/MDIM)

- Colour Temperatures: 2700k - 3000k - 4000k

- Bezel Options: Black (/BK)

- Available with remote Emergency (/RME3/RME3-ST/RME3-PRO)

- Dimensions: 85 x 85mm Depth: 95mm

Product		20'	$\left \right\rangle$	-			
Lamp			4	X			
Lamp Power		sW Blm	/1 76	90*	$\left(\left(\right) \right)$	Ĵ	
Size	85 x 85mm 81 x 81mm						H
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming	- C0/(C1M) 30°		
Colour Tempertature	/827 2700k	/830 3000k		/840 4000k			
Colour	/WH White						
Reflector Options	/BK Black Baffle						GE/5
Emergency	/RME3 Remote Three hour maintained emergency	/RME3-ST Remote three hour m emergency	/RME3-PRO Remote Three hour DALI addressable emergency	v to Sp	Range abbreviation	Wallage	
To Specify: BLT-SQ LED, 14 gear and a black baffle. Pa				omplete with control	ecify	ation	



M	IID/F	RANG	E/5W	/LM,	/DIM	/840,	/OPT	/ME3	3
How to Specify	Style	Range abbreviation	Wattage	Lumens	Driver	Colour Temperature	Options	Emergency	

25-

01268 725086 (Basildon) - www.midlighting.co.uk - 01494 437962 (High Wycombe) - sales@midlighting.co.uk Due to ongoing research and development specifications are subject to change without prior notice. Some availability subject to minimum order All luminaire lumens are 4000k colour temperature readings.