



The IP66 Enterprise luminaire is a linear Hi-bay suitable food processing, warehouses and cold environments.

- A range of lumen outputs from 15,000-62,000lm
- Colour Temperatures: 4000k - 5000k
- Beam Angles: 45°, 90° or 120° (/45D/90D/120D)
- Colour: White or Grey (/WH/GR)
- Available with Dimming (/STD/1-10V)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Mountings: Chain Suspended, Surface mounted or Wire Suspended (/CS/SM/WS)
- IP Rating: IP66
- IK Rating: IK10
- CRI80 as standard, CRI90 Available
- Die cast aluminium alloy housing and a common epoxy resin powder coat
- Dimensions: (Length x Width x Depth)
 - /6 - 678 x 310 x 59mm
 - /13 - 1318 x 310 x 59mm

Industrial

Product	MI-ENT Industrial LED Luminaire							
Light Source	LED							
System Power	/106W 15,000lm	/212W 30,000lm	/122W 19,000lm	/152W 24,000lm	/318W 45,000lm	/424W 60,000lm	/254W 39,000lm	/387W 62,000lm
Size (LxWxH)	/6 678 x 310 x 59mm				/13 1318 x 310 x 59mm			
Driver	/STD Non Dimming				/1-10V 1-10V Dimming			
Colour Temperature	/840 4000k		/940 4000k (CRI 90)		/850 5000k		/950 5000k (CRI 90)	
Colour	/WH White				/GR Grey			
Mountings	/CS Chain Suspension		/SM Surface Mounting			/WS Wire Suspension		
Emergency	/ME3 Three hour maintained emergency		/ME3-ST Three hour maintained self test emergency			/ME3-PRO Three hour DALI addressable emergency		
To Specify: MI-ENT LED, size 678mm, 106W, 120° beam angle, 15,000lm, 4000k, CRI90, Surface mounting with white finish complete with standard control gear. Part code: MI-ENT/106W/15000lm/6/STD/940/120D/WH/SM								

