



**- Low maintenance, affordable and efficient IP65 alternative to the MIS800 LED range, offering an efficacy of up to 85l.lm/cw.**

- LED boards providing lumen outputs of 2633lm
  - Colour Temperatures: 3000k - 4000k
    - Diffuser: Opal
    - IP65 as standard
- Available with microwave sensor for presence detection and presence detector for corridor function available (/MW/CDR)
  - Available with Dimming (/STD/DALI/SDIM)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
  - Dimensions: Ø 430mm x 135mm

Product	MIS/JUP Surface LED circular		
Lamp	LED		
Lamp Power <small>Luminaire lumens (4000K)</small>	/32W 2633lm		
Size Depth	Ø430mm 135mm		
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming
Colour Temperature	/830 3000k		/840 4000k
Colour	/WH White		
Diffuser Options	/OP Opal Diffuser		
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: MIS JUPITER LED, 32W, 4000k, 2633lm LED surface circular finished white supplied complete with DALI control gear and opal diffuser. Part code: MIS/JUP/32W/2633lm/DALI/840/WH/OP			

