



- An anti-ligature surface mounted luminaire suited for IP44 installations in correction centres, hospitals, prisons, care units and other establishments.

- A lumen output of 1000lm
- Colour Temperatures: 3000k - 4000k - 5000k
- Available with Uplight (/UL)
- Available with Night light facility (/NL)
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
 - Diffuser Options: Opal Polycarbonate (/OP)
- Dimensions: 300mm x 300mm x 85mm (L x W x D)
- Available as a circular option (/KEST-C)
- The Kestrel Circular is an anti-ligature fitting
 - A lumen output of 2250lm, 26.2W
 - Colour Temperatures: 3000k - 4000k
 - Available with Dimming (/STD/DALI/SDIM/MDIM)
 - Available with Emergency (/ME3/ME3-ST/ME3-PRO)
 - Diffuser Options: Opal Polycarbonate (/OP)
 - Dimensions: Ø500mm x 116mm (L x D)

| | | | | |
|--|--|---|-------------------------|---|
| Product | MI/KEST/BH Surface LED Luminaire | | | |
| Lamp | LED | | | |
| Lamp Power Luminaire lumens (4000K) | /8.5W 1000lm | | | |
| Size | 300 x 300 x 85mm | | | |
| Driver | /STD Non Dimming | /DALI DALI Dimming | /SDIM Switch Dimming | /MDIM Mains Dimming |
| Colour Temperature | /830 3000k | /840 4000k | | /850 5000k |
| Colour | /WH White | | | |
| Diffuser Options | /OP Opal Diffuser | | | |
| Emergency | /ME3 Three hour main- tained emergency | /ME3-ST Three hour maintained self test emergency | | /ME3-PRO Three hour DALI addressable emergency |
| To Specify: KEST BH LED, 8.5W, 4000k, 1000lm LED surface white supplied complete with standard control gear and opal diffuser. Part code: MI/KEST/BH/LED/8.5W/1000lm/STD/840/WH/OP | | | | |

