



**- A general purpose surface LED luminaire  
ideal for circulation areas.**

- LED boards providing lumen outputs from 941 - 2736lm
  - Colour Temperatures: 3000k - 4000k
  - Diffuser: Opal
- Can also be wire suspended as a pendant (/WS)
- Microwave sensor and presence detector for corridor function available for circulation areas (/MW/CDR)
  - Available with Dimming (/STD/DALI/SDIM)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
  - Dimensions: Ø 425mm x 114mm

Product	MIS800 Surface LED circular			
Lamp	LED			
Lamp Power Luminaire lumens (4000K)	/8W 941lm	/11W 1275lm	/16.5W 1840lm	/26W 2736lm
Size Depth	Ø425mm 114mm			
Driver	/STD Non Dimming	/DALI DALI Dimming		/SDIM Switch Dimming
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White			
Diffuser Options	/OP Opal Diffuser			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency
To Specify: MIS800 LED, 26W, 4000k, 2736lm LED surface circular finished white supplied complete with DALI control gear and opal diffuser. Part code: MIS800/LED/26W/2736lm/DALI/840/WH/OP				

