



**A decorative hand finished pendant, with integrated LED modules to aid Part L compliance. Fitted with a high transmission diffuser for homogeneous illumination.**

- A lumen output of 1615lm
- Colour Temperature: 3000k - 4000k
- Colours: Gloss Red, Satin Black standard or Satin Grey (/RD/BK/GR)
- Dimming is available, please contact technical for more details
- Emergency not available
- Mountings: Wire Suspended as standard, 2M wire suspension cables
- Diffuser: High transmission frosted PMMA diffuser
- Reflector: Raw spun aluminium
- Housing: Raw aluminium with wet spray coat
- Dimensions: (Length x Width x Height) 1320 x 185 x 173mm

Product	MIS/PLA Suspended LED Pendant		
Light Source	LED		
System Power <small>Luminaire lumens (4000K)</small>	/11W 1615lm		
Size	/13 1320mm x 185mm x 173mm		
Driver	/STD Non Dimming	/DIM Contact technical	
Colour Temperature	/830 3000k	/840 4000k	
Colour	/BK Satin Black	/GR Satin Grey	/RD Gloss Red
To Specify: PLANCHE LED, 11W, 4000k, LED suspended finished red supplied complete with standard control gear. Part code: MIS/PLA/11W/1615lm/13/STD/840/RD			

Side Profile View  
Dimensions

