



- Low maintenance, affordable and efficient IP65 alternative to the MIS800 LED range, offering an efficacy of up to 85l.lm/cw.

- LED boards providing lumen outputs of 1869lm
 - Colour Temperatures: 3000k - 4000k
 - Diffuser: Opal
 - IP65 as standard
- Available with microwave sensor for presence detection and presence detector for corridor function available (/MW/CDR)
 - Available with Dimming (/STD/DALI/SDIM)
 - Available with Emergency (/ME3/ME3-ST/ME3-PRO)
 - Dimensions: Ø 350mm x 135mm

Product	MIS/PLU Surface LED circular		
Lamp	LED		
Lamp Power Luminaire lumens (4000K)	/22W 1869lm		
Size Depth	Ø350mm 135mm		
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming
Colour Temperature	/830 3000k		/840 4000k
Colour	/WH White		
Diffuser Options	/OP Opal Diffuser		
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: MIS PLUTO LED, 22W, 4000k, 1869lm LED surface circular finished white supplied complete with DALI control gear and opal diffuser. Part code: MIS/PLU/22W/1869lm/DALI/840/WH/OP			

