



A wire suspended triangle-shaped luminaire, designed to make an architectural statement within any space, thanks to its refined minimal finish.

- A range of lumen outputs from 2211-8845lm
- Colour Temperatures: 3000k - 4000k - TWH
- Colours: White RAL9016, Black 9005 and Silver 9006 as standard, other RAL colours available
- Available with Dimming (/STD/DALI/SDIM)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Distribution: Direct or Indirect /Direct options (/DL/UDL)
- Mountings: Surface mounted or Wire suspended (/SM/WS)
- Diffuser: Opal or Microprism (/OP/MPO)
- Integrated PIR available upon request
- Dimensions: (Width x Height) (Approx. Length)
 - /600 - 50x85mm (600mm)
 - /900 - 50x85mm (900mm)
 - /1200 - 50x85mm (1200mm)

Product	MIS/SPL-TRI Surface or Suspended TRIANGLE-SHAPE LED luminaire								
Light Source	LED								
System Power Luminaire lumens (4000K)	/15.4W 2211lm	/26.1W 3685lm	/31.6W 4423lm	/23.1W 3317lm	/31.1W 4423lm	/47.4W 6635lm	/30.8W 4423lm	/52.2W 7371lm	/63.2W 8845lm
Size	/600 50x85mm			/900 50x85mm			/1200 50x85mm		
Driver	/STD Non Dimming		/DALI DALI Dimming		/SDIM Switch Dimming		/WI Wireless Control		
Colour Temperature	/830 3000k			/840 4000k			/TWH Tunable White		
Colour	/WH White - RAL9016			/BK Black - RAL9005			/SLV Silver - RAL9006		
Diffuser Options	/OP Opal					/MPO Microprism			
Emergency	/ME3 Three hour maintained emergency		/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency		/ME3-WI Three hour Wireless addressable emergency		
To Specify: MIS SPACELINE TRI600, 15.4W, 4000k, 2211lm LED, surface mounted, finished white supplied complete with DALI control gear and opal diffuser. Part code: MIS/SPL-TR/600/15.4W/2211lm/DALI/840/WH/OP/SM									

