



A wire suspended Y-shaped luminaire, designed to make an architectural statement within any space, thanks to its refined minimal finish.

- A range of lumen outputs from 1106-5897lm
- Colour Temperatures: 3000k - 4000k - TWH
- Colours: White RAL9016, Black 9005 and Silver 9006 as standard, other RAL colours available
- Available with Dimming (/STD/DALI/SDIM)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/RME3-WI)
- Distribution: Direct or Indirect/Direct options (/DL/UDL)
- Mountings: Surface mounted or Wire suspended (/SM/WS)
- Diffuser: Opal or Microprism (/OP/MPO)
- Integrated PIR available upon request
- Dimensions: (Width x Height) (Approx. Diameter)
 - /600 - 50x85mm (Ø600mm)
 - /900 - 50x85mm (Ø900mm)
 - /1200 - 50x85mm (Ø1200mm)

Product	MIS/SPLY Surface or Suspended Y-SHAPE LED luminaire								
Light Source	LED								
System Power Luminaire lumens (4000K)	/7.7W 1106lm	/15.8W 2212lm	/21.5W 2950lm	/11.6W 1659lm	/23.7W 3318lm	/32W 4425lm	/15.4W 2211lm	/31.6W 4423lm	/42.8W 5897lm
Size	/600 50x85mm			/900 50x85mm			/1200 50x85mm		
Driver	/STD Non Dimming		/DALI DALI Dimming		/SDIM Switch Dimming		/WI Wireless Control		
Colour Temperature	/830 3000k			/840 4000k			/TWH Tunable White		
Colour	/WH White - RAL9016			/BK Black - RAL9005			/SLV Silver - RAL9006		
Diffuser Options	/OP Opal					/MPO Microprism			
Emergency	/ME3 Three hour maintained emergency		/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency		/ME3-WI Three hour Wireless addressable emergency		
To Specify: MIS SPACELINE Y, LED, 7.7W, 4000k, 1106lm LED surface mounted, finished white and supplied complete with DALI control gear and opal diffuser. Part code: MIS/SPLY/600/7.7W/1106lm/DALI/840/WH/OP/SM									

