



## A wire suspended Hexagon-shaped luminaire, designed to make an architectural statement within any space, thanks to its refined minimal finish.

- A range of lumen outputs from 2212-11793lm
- Colour Temperatures: 3000k 4000k TWH
- Colours: White RAL9016, Black 9005 and Silver 9006 as standard, other RAL colours available
- Available with Dimming (/STD/DALI/SDIM)
- -Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- -Wireless Emergency (/ME3-WI)

- Distribution: Direct or Direct/Indirect options (/DL/UDL)

**IP20** 

PART

- Mountings: Surface or Wire suspended (/SM/WS)
- Diffuser: Opal or Microprism (/OP/MPO)
- Integrated PIR available upon request
- Dimensions: (Width x Height) (Approx. Diameter)
- /600 50x85mm (Ø600mm)
- /900 50x85mm (Ø900mm)
- /1200 50x85mm (Ø1200mm)

Product	MIS/SPL-HEX Surface or Suspended HEXAGON-SHAPE LED luminaire									
Light Source	LED									
System Power Luminaire lumens (4000K)	/15.5W 2212lm	/29.5W 4425Im	/42.9W 5899Im	/23.3W 3318lm	,		/64.2W 8846lm	/41.4W 5897lm	/63.2W 8845Im	/85.6W 11793lm
Size	/600 50x85mm			/900 50x85mm				/1200 50x85mm		
Driver	/STD Non Dimming		D	/DALI DALI Dimming		/SDIM Switch Dimr		ning	/WI ing Wireless Control	
Colour Temperature	/830 3000k			/840 4000k			· /		/TWH Tunable White	
Colour	/WH White - RAL9016			/BK Black - RAL9005			/SLV Silver - RAL9006			
Diffuser Options	/OP Opal					/MPO Microprism				
Emergency				T hour maintained st emergency		/ME3-PRO Three hour DALI ddressable emergency		· I	/ME3-WI Three hour Wireless addressable emergency	
To Specify: MIS SPACELINE H and opal diffuser. Part code:							te supplied o	complete v	vith DALI contro	ol gear

