



The TRK-1 is a track luminaire with a sleek, minimalistic design, ideally suited for retail, hospitality and leisure environments. Compatible with Global Trac® systems. Visit www.midlighting.co.uk for full track details.

- A lumen outputs of 1200lm or 2300lm
- Colour Temperatures: 3000k - 4000k
- Beam Angles : 12°, 18°, 25° or 40° (/12D/18D/25D/40D)
- Colours: White or Black (/WH/BK)
- Available with Dimming (/STD/DAL)
- Refer to track system page 84 for the following mountings, Surface, Recessed and Wire suspended
- TRK-1 head rotates 355 degrees and pivots through 90 degrees. The rotating position can be set by the scale marked on the connection to the body.
- CRI80 as standard, CRI90 Available
- Dimensions: (Diameter x Height) Ø72 x137mm

| | | | | |
|--|---|----------------------|-----------------------|----------------------|
| Product | MI/TRK-1 LED TRK Spotlight | | | |
| Light Source | LED | | | |
| System Power <small>Luminaire lumens (4000K)</small> | /15W 1200lm | | /28W 2300lm | |
| Size | Ø72 x137mm | | | |
| Driver | /STD Non Dimming | | /DALI DALI Dimming | |
| Colour Temperature | /830 3000k | /930 CRI 90 3000k | /840 4000k | /940 CRI 90 4000k |
| Colour | /WH White | | /BK Black | |
| Beam Angle | /12D 12 Degrees | /18D 18 Degrees | /25D 25 Degrees | /40D 40 Degrees |
| Emergency | Remote EMLED TRK available. See Page 263 for details. | | | |
| To Specify: TRK-1, 28W, 4000k, 2300lm, 18 degree beam angle, LED track spotlight supplied with DALI control gear and finished in black. Part code: MI/TRK-1/28W/2300lm/DALI/840/18D/BK | | | | |

