



- Low maintenance, affordable and efficient IP44 LED bulkhead luminaire. Designed with a unique replaceable gear tray and integral sensor options.

- LED boards providing a range of lumen outputs of 1500-3000lm
 - Colour Temperature: 4000k
 - Diffuser: Opal
 - IP44 as standard
- Available with microwave sensor for presence detection and presence detector for corridor function available (/MW/CDR)
 - Available with Dimming (/STD/DALI)
 - Available with Emergency (/ME3/ME3-ST/ME3-PRO)
 - Dimensions: Ø 400mm x 107mm

Product	MIS/VENUS Surface LED circular		
Lamp	LED		
Lamp Power	/22W 1500lm	/42W 3000lm	
Size Depth	Ø400mm 107mm		
Driver	/STD Non Dimming		/DALI DALI Dimming
Colour Temperature	/840 4000k		
Colour	/WH White		
Diffuser Options	/OP Opal Diffuser		
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: MIS VENUS LED, 22W, 4000k, 1500lm LED surface circular finished white supplied complete with DALI control gear and opal diffuser. Part code: MIS/VENUS/22W/1500lm/DALI/840/WH/OP			

