



An architectural, square, IP65, ultra-shallow LED solution. Semi-Recessed; ideal for restricted voids.

- A range of lumen outputs from 556-2347lm
- Colour Temperatures: 3000k - 4000k - 6500k
- Colours: White (/WH)
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with emergency (/RME3/RME3-ST/RME3-PRO)
- Wireless Emergency (/RME3-WI)
- Diffuser: Opal
- IP Rating: IP65
- Shallow Depth: 20mm (depth without driver, driver depth may vary)
- Dimensions: (Length x Width) See table below
- Cut-out Dimensions: (Diameter) See table below

Product	MIR/WAF-P/SQ Semi-Recessed WAFER-P Square				
Light Source	LED				
System Power Luminaire lumens (4000K)	/8W 556lm	/11W 855lm	/15W 1066lm	/22W 1507lm	/30W 2347lm
Size Cut-out	100 x 100mm Ø 80mm	125 x 125mm Ø 105mm	155 x 155mm Ø 135mm	185 x 185mm Ø 165mm	215 x 215mm Ø 195mm
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming	/WI Wireless Control
Colour Temperature	/830 3000k		/840 4000k		/865 6500k
Bezel Colour	/WH White				
Diffuser Options	/OP Opal Diffuser				
Emergency	/RME3 Remote three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency	/RME3-PRO Remote three hour DALI addressable emergency	/RME3-WI Remote three hour Wireless addressable emergency	
To Specify: WAFER-P SQUARE LED, 15W, 4000k, 1066lm LED semi-recessed downlight finished white complete with remote control gear. Part code: MIR/WAF-P/SQ/15W/1066lm/STD/840/WH/OP					

