



- A narrow, cost effective LED downlight with a shallow profile the 10STAR offers excellent glare control whilst producing a high light output.

- The product is available in a variation of star configurations, if you have a specific requirement please contact technical.

- 28W providing a lumen output of 2240lm
 - Colour Temperatures: 3000k - 4000k
 - Beam Angle: 48 Degrees as standard.
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Bezel Options: Black bezel (/BK), Black/White Trim (/BK/WH)
 - Dimensions 281 x 44 x 55mm (L x W x D)
 - Cut-out Dimensions 273 x 36mm (L x W)

Product	MID/10STAR Recessed LED Downlight			
Lamp	LED			
Lamp Power <small>Luminaire lumens (4000K)</small>	/28W 2240lm			
Size Cut-out	281 x 44 x 55mm 273 x 36mm			
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming
Colour Temperature	/830 3000k		/840 4000k	
Bezel Colour	/BK Black			
Trim Options	/BK Black		/WH White	
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency
To Specify: 10STAR LED, 28W, 4000k, 1957lm LED downlight finished black supplied with DALI dimming control gear. Part code: MID/10STAR/28W/2240lm/DALI/840/BK/BK				

