



Downlight

Up/Downlight

**- The ADA-2 is a High Output IP66 Direct/Indirect decorative, robust wall mounted amenity luminaire and black powdercoat finish.**

- Providing a nominal lumen output of 2300lm or 4400lm
  - Colour Temperature: 4100k
- Rated IP66 - Die cast aluminium fixing base and frames.
- Emergency Version Available (/ME3, /ME3-ST, /ME3-Pro)
  - Suitable for BESA box fixings.
- Clear glass lens. - Both Down or Up/Downlight with Beam Selection
  - Black powdercoat polyester finish over epoxy powder as standard. Other colours available.
- Dimensions: 146mmØ, 226mm x 316mm(Up/Down), 260mm(Down) ( Diameter x Depth x Height )

Product	MI/ADA-2 Wall IP66 LED Luminaire		
Lamp	LED		
System Power Luminaire lumens (4100K)	/40W/UD 4400lm	/20W/D 2300lm	
Size	146Ø x 226mm x 316mm (Up/Down), 260mm (Down) Diameter, Depth, Height		
Driver	/STD Non Dimming		
Colour Temperature	/840 4100k		
Beam Angle Up	/UN Narrow 30°	/UM Medium 70°	/UW Wide 100°
Beam Angle Down	/DN Narrow 30°	/DM Medium 70°	/DW Wide 100°
Colour	/BK Black		
To Specify: ADA-2, 40W, 4400lm, 4000k, Wide Beam UP, Medium Beam Down wall mounted luminaire finished black with standard integral control gear. Part code: MI/ADA2/40W/UD//4400lm/STD/840/UW/DM/BK			

