



The ADA-SQ features a die-cast aluminium base with an extruded aluminium body, a super white tempered glass lens for visual comfort, and a UV-protected powder-coated finish for excellent corrosion resistance.

- A range of lumen outputs from 990 - 4100lm
 - Colour Temperature: 3000k
 - Colours: Black as standard (/BK), other RAL's available
 - Standard Non Dimming (/STD)
 - Emergency not available
 - Mountings: Wall Mounted
 - IP Rating: IP65
 - Lens: Tempered frosted glass lens
 - Distribution: Direct or Direct/Indirect (/DL/UDL)
 - Housing: Die-cast aluminium
 - Dimensions: (Length x Width x Height)
- See table below as per wattage or distribution

Exterior

Product	MI/ADA-SQ A Square Wall Mounted IP65 LED Luminaire			
Light Source LED	/DL Direct (Downlight)		/UDL Direct/Indirect (Up & downlight)	
System Power Luminaire lumens (3000K)	/10W 990lm	/23W 2350lm	/20W 2300lm	/36W 4100lm
Size (Length x Width x Height)	100 x 100 x 150mm	150 x 150 x 170mm	100 x 100 x 150mm	50 x 150 x 170mm
Driver	/STD Non Dimming			
Colour Temperature	/730 3000k			
Colour	/BK Black			
Emergency	n/a			
To Specify: ADA-SQ, direct distribution, 10w, 100 x 100 x 150mm with standard non dimming , 3000K colour temperature and finished in black, Part code: MI/ADA-V2/10W/990lm/STD/730/DL/BK				

ADA-SQ 23W & 36W



MIR/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3

How to Specify

Style
Range abbreviation
Wattage
Lumens
Size
Driver
Colour Temperature
Options
Emergency