



**The ADA-V2 features a die-cast aluminium base with an extruded aluminium body, a super white tempered glass lens for visual comfort, and a UV-protected powder-coated finish for excellent corrosion resistance.**

- A range of lumen outputs from 960 - 8400lm
  - Colour Temperature: 4000k
  - Colours: Black as standard (/BK), other RAL's available
  - Beam Angle: 80 Degrees
  - Standard Non Dimming (/STD)
  - Remote Emergency: (/RME3/RME3-ST/RME3-PRO)
  - Mountings: Wall Mounted
  - IP Rating: IP65
  - Lens: Tempered glass lens
  - Distribution: Direct or Direct/Indirect (/DL/UDL)
  - Housing: Die-cast aluminium
  - Dimensions: (Diameter x Height)
- See table below as per wattage or distribution

|   |  |                 |   |  |  |                 |
|---|--|-----------------|---|--|--|-----------------|
| Product   | MI/ADA-V2<br>Wall Mounted IP65 LED Luminaire         |                 |   |  |  |                 |
| Light Source LED  | /DL<br>Direct (Downlight)                            |                 |   | /UDL<br>Direct/Indirect (Up & downlight) |  |                 |
| System Power<br>Luminaire lumens (4000K)  | /12W<br>960lm  | /18W<br>1940lm  | /40W<br>4000lm  | /18W<br>1560lm                           | /40W<br>4360lm   | /80W<br>8400lm  |
| Size<br>(Dia x Height)  | Ø110 x<br>166mm                                      | Ø144 x<br>204mm | Ø200 x<br>320mm   | Ø110 x<br>168mm                          | Ø144 x<br>226mm  | Ø200 x<br>408mm |
| Driver  | /STD<br>Non Dimming                                  |                 |   |  |  |                 |
| Colour Temperature  | /740<br>4000k  |                 |   |  |  |                 |
| Colour  | /BK<br>Black   |                 |   |  |  |                 |
| Emergency   | /RME3<br>Remote Three hour main-<br>tained emergency |                 | /RME3-ST<br>Remote Three hour main-<br>tained self test emergency |  | /RME3-PRO<br>Remote Three hour DALI<br>addressable emergency |                 |
| To Specify: ADA-V2, direct distribution, 12w, Ø110mm with standard non dimming , 4000K colour temperature and finished in black, Part code: MI/ADA-V2/12W/960lm/STD/740/DL/BK |  |                 |   |  |  |                 |

MIR/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3

How to Specify

Style  
Range abbreviation  
Wattage  
Lumens  
Size  
Driver  
Colour Temperature  
Options  
Emergency