



**The AERO-C-V2 is a modern pole-mounted luminaire ideal for parks, pathways, and open spaces. Designed for Ø60mm poles, it offers multiple light distributions, a UV-resistant finish, and compatibility with smart control systems.**

- A lumen output of 3,120lm or 11,400lm
- Colour Temperature: 3000k - 4000k
- Colours: Black as standard (/BK), other RAL's available
- Available with Dimming (/STD/DALI)
- Emergency not available
- Mounting: Pole Mounting on a Ø60mm poles
- Arm Bracket Options: Single or Twin (/S/T)
- IP Rating: IP66
- Distributions: (/T1/T2)
- Lens: Tempered glass lens with Polycarbonate reflector
- Housing: Die-cast aluminium
- Dimensions of Head: (Diameter x Length x Width) Ø490 x 610 x 84mm

Exterior

Product	MI/AERO-C-V2 IP66 LED Pole Mounted Luminaire							
Light Source	LED							
System Power <small>Luminaire lumens (4000K)</small>	/24W 3120lm	/40W 5640lm	/60W 8410lm	/80W 11,400lm	/24W 3150lm	/40W 5690lm	/60W 8510lm	/24W 11,120lm
Arm Brackets	/S Single Arm Bracket				/T Twin Arm Bracket			
Distribution <small>Optic purpose</small>	/T1 SYM AREA				/T2 Walkways and streets			
Driver	/STD Non Dimming				/DALI DALI Dimming			
Size <small>(Diameter x Length x Width)</small>	Ø490 x 610 x 84mm							
Colour Temperature	/730 3000k				/740 4000k			
Colour	/BK Black							
To Specify: AERO-C V2, 24W, 3120lm, 4000k, with twin arms LED through pole mounted, finished black, a symmetrical light distribution, black and supplied with standard integral control gear. Part code: MI/AERO-C-V2/24W/3120lm/S/STD/840/T1/BK								

