



- A cost effective surface or suspended extruded system ideally suited for modular or continuous runs.

This system utilises the wattages of the LEXLED range.

- 4.8W-M - 9.6 W-M - 14.4W-M - 19.6W-M options
- Available with LED boards for a high efficiency option. Please contact technical for further details.
 - Available with Dimming (/STD/DALI/SDIM/MDIM)
 - Colour Temperatures: 2700k - 3000k - 4000k - RGBW
 - Available with a CRI90 option (Standard CRI80) (/9CT)
- Available in IP20 as standard or as IP67 (/IP67) (LED Tape only)
 - Dimensions: Length required x 55mm x 76mm
- Surface mounted as standard, wire suspension kit available (/WS)

Product	MIS/AIRLINE Linear LED Luminaire			
Lamp	LED			
Lamp Power	/4.8W-M 410lm/M	/9.6W-M 860lm/M	/14.4W-M 1050m/M	/19.6W-M 1900lm/M
Size	Length required x 55 x 76mm			
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming
Colour Temperature	/827 2700k	/830 3000k	/840 4000k	/RGBW Colour changing
Length	/2M* * Required length			
Emergency	/RME3 Remote Three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency		/RME3-PRO Remote Three hour DALI addressable emergency
To Specify: AIRLINE, 19.6W-M, 4000k, 1900m/M, Airline extrusion supplied with LED tape and DALI control gear, opal diffuser, 6 metres* in length, complete with wire suspension kit. Part code: MIS/AIRLINE/19.6W-M/1900lm-M/DALI/840/2M/OP/WS *2M Length is shown as an example. Should you require different lengths please specify the length in the part code.				

