

ALULINE50



- A high quality recessed extruded system ideally suited for modular or continuous runs.

- Colour Temperatures: 3000k - 4000k - 6000k
 - Body: Aluminium Extrusion
 - Body Options: Trimmed /Plaster-in (/T/P)
- White RAL9016, Black 9005 and Silver 9006 as standard, other RAL colours available
- Available with Dimming (/STD/DALI/SDIM)
- Available in Emergency (/ME3/ME3-ST/ME3-PRO)
- Diffuser: Polar White (/PW)
- Depth: 80mm
- Available in continuous runs with aluminium infills. Please contact our technical department for further details

Product	MIR/ALU50 Recessed LED Linear			
Lamp	LED			
Lamp Power Luminaire lumens (4000K)	/19W 2081lm	/31W 3330lm	/24W 2605lm	/39W 4169lm
Size	/12 1200 x 60mm		/15 1500 x 60mm	
Driver	/STD Non Dimming	/DALI DALI Dimming		/SDIM Switch Dimming
Colour Temperature	/830 3000k	/840 4000k		/860 6000k
Colour	/WH White - RAL9016	/BK Black - RAL9005		/SLV Silver - RAL9006
Diffuser Options	/PW Polar White Diffuser			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency
To Specify: ALULINE 50 LED, trimmed, 24W, 4000k, 2605lm LED linear recessed finished white supplied complete with DALI control gear and polar white diffuser. Part code: MIR/ALU50/T/LED/24W/2605lm/12/DALI/840/WH/PW				

