

# APOLLO G6



**A cost effective, high quality LED downlight, the Apollo clear and opal glass has a range of interchangeable reflectors.**

**The G6 & G7 (830/840) are stock options. Other options available to order.**

- A range of lumen outputs from 2100-3000lm
- Colour Temperatures: 3000k - 4000k
- Additional wattages and lumen outputs available, please contact technical for further details
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available in Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Diffuser Options: Clear Glass/ Opal (/CL/OP)
- Reflector Options: Silver, White or Black (/SLV/WH/BK)
- Dimensions: (Diameter x Depth)  
Ø180 x 111mm
- Cut-out Dimensions: (Diameter) Ø150mm

Product	MID/APL/G6 Recessed APOLLO Downlight				
Light Source	LED				
System Power <small>Luminaire lumens (4000K)</small>	/21W 2300lm	/28W 3000lm	/21W 2100lm	/28W 2800lm	
Diffuser Options	/CL Clear Glass		/OP Opal		
Size Cut-out	Ø 180mm Ø 150mm				
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming	/WI Wireless Control
Colour Temperature	/830 3000k		/840 4000k		
Reflector Colour	/WH White	/SLV Silver		/BK Black	
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency	
<small>To Specify: APOLLO G6 LED, 21W, 4000k, 2100lm LED downlight finished white supplied with an opal glass reflector. Part code: MID/APL/G6/21W/2100lm/840/WH/OP Clear reflector 4000k lumen figures only. Opal reflector 4000k lumen figures only.</small>					

### Reflector Options

