





















A cost effective, high quality LED downlight, the Apollo clear and opal glass has a range of interchangeable reflectors. The G6 & G7 (830/840) are stock options. Other options available to order.

- A range of lumen outputs from 2800-4300lm
- Colour Temperatures: 3000k 4000k
- Additional wattages and lumen outputs available, please contact technical for further details
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available in Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)

- Diffuser Options: Clear Glass/ Opal (/CL/OP)
- Reflector Options: Silver, White or Black (/SLV/WH/BK)
- Dimensions: (Diameter x Depth)

Ø230 x 143mm

- Cut-out Dimensions: (Diameter) Ø205mm

Product	MID/APL/G8 Recessed APOLLO Downlight							
Light Source	LED							
System Power Luminaire lumens (4000K)	/28W 3000lm		/42W 4300lm		/28W 2800lm		/42W 3900lm	
Diffuser Options	/CL Clear Glass				/OP Opal			
Size Cut-out	Ø 230mm Ø 205mm							
Driver	/STD Non Dimming	/DALI DALI Dimming		,	DIM Dimming	/MDIM Mains Dimn	ning	/WI Wireless Control
Colour Temperature	/830 3000k				/840 4000k			
Reflector Colour	/WH White			/S Sil			/BK Black	
Emergency	/ME3 Three hour maintained emergency		/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency		/ME3-WI Three hour Wireless addressable emergency	

To Specify: APOLLO G8 LED, 28W, 2800lm, 4000k LED downlight finished white supplied with an opal glass reflector. Part code: MID/APL/G8/28W/2800lm/840/WH/OP Clear reflector 4000k lumen figures only. Opal reflector 4000k lumen figures only.

Reflector Options



SILVER



WHITE



