



**- Low maintenance, affordable and efficient batten LED luminaire.**  
**An energy efficient and high output alternative to T5 fluorescent lamps.**

- LED boards providing lumen outputs of 1869lm-4526lm
  - Colour Temperatures: 3000k - 4000k - 5000k
- Diffuser: High transmission opal or semi transparent frosted cover (/OP/FC)
  - RAL 9016 as standard. Painting to RAL colours available.
- Available with microwave sensor and PIR for presence detection (/MW/PIR)
  - Available with Dimming (/STD/DALI/SDIM)
  - Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Dimensions: 1200 x 56 x 76mm (L x W x H) (600/1500mm options available upon request)

Product	MIB Surface LED linear		
Lamp	LED		
Lamp Power Luminaire lumens (4000K)	/35W 3570lm	/39W 3971lm	/50W 4526lm
Size	/12 1200mm		
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming
Colour Temperature	/830 3000k	/840 4000k	/850 5000k
Colour	/WH White - RAL 9016		
Diffuser Options	/OP High transmission opal		/FC Semi transparent frosted cover
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: BATTEN LED, 50W, 4000k, 4526lm LED surface linear finished white RAL9016 supplied complete with DALI control gear and opal diffuser. Part code: MIB/LED/50W/4526lm/12/DALI/840/WH/OP			

