




**A low glare architectural downlight with a square minimal bezel. Fitted with integral IP44 protective lens and a deep matt black bezel to minimise glare.**

- A lumen output of 627lm or 811lm
- Colour Temperatures: 2700k - 3000k - 4000k
- Colours: White or Black (/WH/BK)
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
- Wireless Emergency (/RME3-WI)
- Bezel Options: Black or White (/BK/WH)
- IP Rating: IP44
- Dimensions: (Length x Width x Depth)  
85 x 85 x 95mm
- Cut-out Dimensions: (Length x Width)  
81 x 81mm

Product	MID/BLT-SQ Recessed LED Downlight			
Light Source	LED			
System Power Luminaire lumens (4000K)	/6.7W 627lm			/8.2W 811lm
Size Cutout	85 x 85mm 81 x 81mm			
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming  /WI Wireless Control
Colour Temperature	/827 2700k	/830 3000k	/840 4000k	
Colour	/WH White			
Bezel Options	/BK Black Baffle		/WH White Baffle	
Emergency	/RME3 Remote three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency	/RME3-PRO Remote three hour DALI addressable emergency	/RME3-WI Remote three hour Wireless addressable emergency
To Specify: BLT-SQ LED, 6.7W, 4000k, 627lm LED downlight luminaire finished white supplied complete with control gear and a black bezel. Part code: MID/BLT-SQ/6.7W/627lm/STD/840/WH/BK				



MIR/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3

How to Specify

- Style
- Range abbreviation
- Wattage
- Lumens
- Size
- Driver
- Colour Temperature
- Options
- Emergency