



- A low glare architectural downlight with a square minimal bezel. Fitted with integral IP44 protective lens and a deep matt black bezel to minimise glare.

- Available in 8 & 14 watts
 - 593/895umens
 - IP44 as standard
- Available with Dimming (/STD/DALI/SDIM/MDIM)
 - Colour Temperatures: 2700k - 3000k - 4000k
 - Bezel Options: Black/White (/BK/WH)
- Available with remote Emergency (/RME3/RME3-ST/RME3-PRO)
 - Dimensions: 85 x 85mm Depth: 95mm

Product	MID/BLT-SQ Recessed LED Downlight			
Lamp	LED			
Lamp Power <small>Luminaire lumens (4000K)</small>	/8W 593lm			/14W 895lm
Size Cutout	85 x 85mm 81 x 81mm			
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming
Colour Temperature	/827 2700k	/830 3000k		/840 4000k
Colour	/WH White			
Bezel Options	/BK Black Baffle		/WH White	
Emergency	/RME3 Remote Three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency		/RME3-PRO Remote Three hour DALI addressable emergency
To Specify: BLT-SQ LED, 14W, 4000k, 895lm LED downlight luminaire finished white supplied complete with control gear and a black bezel. Part code: MID/BLT-SQ/14W/895lm/STD/840/WH/BK				

