




Flange Detail with Root


- The BOLLOVARD is an IP65 decorative bollard with a clear inner lens and no upright cutoff.
The bollard has an internal ballast tray for ease of maintenance.

- Providing a lumen output of 674lm
- Colour Temperature: 4000k - 180 Degree Shield (/180DS)
- Extruded aluminium body - Rated IP65
- Clear polycarbonate vandal-resistant lens - Microwave Sensor Option (/MW)
- Mount kit with 200mm anchor bolts (included).
- Available as Root or Flange mounted, (Flange is required for Root Mounting option), (/RT/FL)
- Flat top, black powdercoat finish over chromate conversion coating (/BK)
- Dimensions: 1019mm x Ø120mm (L x D)

Product	MI/BOLV Bollard IP65 LED Luminaire		
Lamp	LED		
System Power <small>Luminaire lumens (4000K)</small>	/18.9W 674lm		
Size	1019mm x Ø120mm		
Driver	/STD Non Dimming		
Colour Temperature	/840 4000k		
Colour	/BL Black		
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: BOLV LED, 18.9W, 674lm, 5000k, LED bollard anchor root mounted luminaire finished black supplied with complete with standard integral control gear. Part code: MI/BOLV/18.9W/674lm/STD/840/BK/RT			



Full 360 Degree Distribution as Standard



Exterior