



**- Low maintenance, affordable and efficient IP65 LED bulkhead luminaire. Designed with a unique replaceable gear tray and integral sensor options.**

- LED boards providing a range of lumen outputs of 1000-1500lm

- Colour Temperature: 4000k

- Diffuser: Opal

- IP65 as standard

- Available with microwave sensor for presence detection and presence detector for corridor function available (/MW/CDR)

- Available with Dimming (/STD/DALI)

- Available with Emergency (/ME3/ME3-ST/ME3-PRO)

- Dimensions: Ø 370mm x 100mm

Product	MIS/CHALLENGER Surface LED circular		
Lamp	LED		
Lamp Power	/15W 1100lm	/22W 1500lm	
Size Depth	Ø370mm 100mm		
Driver	/STD Non Dimming		/DALI DALI Dimming
Colour Temperature	/840 4000k		
Colour	/WH White		
Diffuser Options	/OP Opal Diffuser		
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: MIS CHALLENGER LED, 22W, 4000k, 1500lm LED surface circular finished white supplied complete with DALI control gear and opal diffuser. Part code: MIS/CHALLENGER/22W/1500lm/DALI/840/WH/OP			

