

# DOME D200



**A high quality LED downlight, the Dome D200 is designed for efficiency and functionality with its sleek exterior aluminium powdered coat.**

- A range of lumen outputs from 4100- 6800lm
- Colour Temperatures: 2700k - 3000k - 4000k
- Beam Angle: 18° to 70° Options
- Available with Dimming (/STD/DALI/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Reflector Options: Black, Grey or White
- IP Rating: IP54
- CRI80 as standard, CRI90 Available
- Aluminium Powder coating
- Dimensions: (Diameter x Height)  
Ø218mm x 132mm
- Cut-out Dimension: (Diameter) Ø200mm

Product	MID/DOME/D200 DOME Downlight				
Light Source	LED				
System Power <small>Luminaire Lumens (4000K)</small>	/28W 4100lm	/42W 5600lm	/56W 6800lm		
Size <small>(cut-out size)</small>	Ø218mm x 132mm Ø200mm				
Driver	/STD Non Dimming	/DALI DALI Dimming	/MDIM Mains Dimming	/WI Wireless Control	
Colour Temperature	/827 2700k	/830 3000k		/840 4000k	
Reflector Colour	/BK Black		/WH White	/GR Grey	
Beam Angle Options	/18D 18 Degree	/25D 25 Degree	/30D 30 Degree	/50D 50 Degree	/70D 70 Degree
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour wireless addressable emergency	
To Specify: DOME, D200, 28W, 4000k, 4100lm, DALI Dimming, 30 Degrees LED downlight finished white Part code: MID/DOME/D200/28W/4100lm/DALI/840/30D/WH					

### Reflector Options

