

DOME D200



A high quality LED downlight, the Dome D200 is designed for efficiency and functionality with its sleek exterior aluminium powdered coat.

- A range of lumen outputs from 4100- 6800lm
- Colour Temperatures: 2700k - 3000k - 4000k
- Beam Angle: 18° to 60° Options
- Available with Dimming (/STD/DALI/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Reflector Options: Black, Grey or White
- IP Rating: IP54
- CRI80 as standard, CRI90 Available
- Aluminium Powder coating
- Dimensions: (Diameter x Height)
Ø218mm x 132mm
- Cut-out Dimension: (Diameter) Ø200mm

Product	MID/DOME/D200 DOME Downlight				
Light Source	LED				
System Power Luminaire lumens (4000K)	/28W 4100lm	/42W 5600lm		/56W 6800lm	
Size (cut-out size)	Ø218mm x 132mm Ø200mm				
Driver	/STD Non Dimming	/DALI DALI Dimming		/MDIM Mains Dimming	/WI Wireless Control
Colour Temperature	/827 2700k		/830 3000k		/840 4000k
Reflector Colour	/BK Black		/WH White		/GR Grey
Beam Angle Options	/18D 18 Degree	/25D 25 Degree	/30D 30 Degree	/50D 50 Degree	/60D 60 Degree
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour wireless addressable emergency
To Specify: DOME, D200, 28W, 4000k, 4100lm, DALI Dimming, 30 Degrees LED downlight finished white Part code: MID/DOME/D200/28W/4100lm/DALI/840/30D/WH					

Reflector Options



MIR/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3

