

DOME D75



A high quality LED downlight, the Dome D75 is designed for efficiency and functionality with its sleek exterior aluminium powdered coat.

- A lumen outputs of 1100lm or 1400lm
- Colour Temperatures: 2700k - 3000k - 4000k
- Beam Angle: 18° to 50° Options
- Available with Dimming (/STD/DALI/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Reflector Colours: Black, Grey and White
- IP Rating: IP54
- CRI80 as standard, CRI90 Available
- Aluminium Powder coating
- Dimensions: (Diameter x Height)
Ø84 x 72mm
- Cut-out Dimension: (Diameter) Ø75mm

Product	MID/DOME/D75 DOME Downlight			
Light Source	LED			
System Power Luminaire lumens (4000K)	/9W 1100lm		/13W 1400lm	
Size (cut-out size)	Ø84 x 72mm Ø75mm			
Driver	/STD Non Dimming	/DALI DALI Dimming	/MDIM Mains Dimming	/WI Wireless Control
Colour Temperature	/827 2700k		/830 3000k	/840 4000k
Reflector Colour	/BK Black		/WH White	/GR Grey
Beam Angle Options	/18D 18 Degree	/25D 25 Degree	/30D 30 Degree	/50D 50 Degree
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour wireless addressable emergency
To Specify: DOME, 75, 13W,1400lm, 4000k, DALI Dimming, 30 Degrees, LED downlight finished white Part code: MID/DOME/D75/13W/1400lm/DALI/840/WH/30D				

Reflector Options

