



The ECLIPSE is a compact and stylish LED downlight designed for areas where space is limited. With a small 50mm cut-out, it's ideal for discreet lighting installations and can be plastered in to create a clean, minimal finish.

- A lumen output of 834lm
 - Colour Temperatures: 2700K - 3000K - 4000K
 - Colour: White, Black or Silver (/WH/BK/SLV)
 - Dimming not available
 - Beam Angle: (10D/15D/28D/40D)
 - Emergency not available
 - Mounting: Recessed Trimmed as standard, Plastered-In (/PI)
- IP Rating: IP20
 - CRI90 as standard
 - Dimensions: (Diameter x Length)
Ø55 x 86mm
 - Cut-out Dimensions: (Diameter)
Ø50mm

Product	MID/ECLIPSE Recessed Small LED Downlight			
Light Source	LED			
System Power Luminaire lumens (3000K)	/8W 834lm			
Size Cut-out	Ø40mm x 83mm Ø35mm			
Driver	/STD Non Dimming			
Colour Temperature	/827 2700K	/830 3000K		/840 4000K
Bezel Colour	/WH White	/BK Black		/SLV Silver
Beam Angle	/10D 10° Beam Angle	/15D 15° Beam Angle	/28D 28° Beam Angle	/40D 10° Beam Angle
Emergency	n/a			
To Specify: The Eclipse, 8W, 834lm, 3000K, LED downlight finished white. supplied with a 40° beam angle, and standard non dimming. Part code: MID/ECLIPSE/8W/834lm/STD/830/WH				

Plastered-In Version
(/PI)



MIR/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3

How to Specify

Style

Range abbreviation

Wattage

Lumens

Size

Driver

Colour Temperature

Options

Emergency