



The ECOLINE is a part-L compliant industrial light design for data centres, corridors, warehouses and amenities. Sealed to IP65 or IP66, it is also suitable for exterior applications.

Industrial

- A range of lumen outputs from 1500-9150lm
- Colour Temperatures: 3000k - 4000k - 6500k
- Colour: White
- Available with Dimming (/STD/DALI/1-10V)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Mountings: Suspended with stainless steel brackets as standard, surface or trunking mounted (/WS/SM/TM)
- Available with sensors (contact technical for more info)
- Diffuser: Frosted Opal
- IP Rating: IP65 as standard, IP66 available (/IP66)
- IK Rating: IK08
- Housing: Frosted polycarbonate, with 1 or 2 open end caps.
- Dimensions: (Length x Width x Height)
See Length in table below x 88 x 81 mm

Product	MIS/ECOLINE Industrial Linear LED Luminaire				
Light Source	LED				
System Power Luminaire lumens (4000K)	/12W 1500lm	/28W 3780lm	/35W 4575lm	/42W 5670lm	/70W 9150lm
Length	/6 620mm	/12 1190mm	/15 1490mm	/18 1790mm	/30 2950mm
Driver	/STD Non Dimming		/DALI DALI Dimming		/1-10V 1-10V Dimming
Colour Temperature	/830 3000k		/840 4000k		/865 6500k
Colour	/WH White				
Diffuser	/OP Frosted Opal				
Emergency	/ME3 Three hour maintained emergency		/ME3-ST Three hour maintained self test emergency		/RME3-PRO Three hour DALI addressable emergency
To Specify: ECOLINE, 12W, 1500lm, 620mm length, 4000k, LED suspended finished white as standard, complete with DALI control gear. Part code: MIS/ECOLINE/12W/1500lm/6/DALI/840/WH/OP					

ECOLINE Dimensions

