



The ELLE is a compact, wall-mounted luminaire designed for perimeters and walkways. Its 45° angled body directs light downward, with a clean bezel trim and tamper-resistant screws. Photocell and emergency options available.

- A lumen output of 1500lm
- Colour Temperature: 3000k - 4000k
- Colour: Black(/BK)
- Standard non dimming available (/STD)
- Emergency Options (/ME3/ME3-ST/ME3-PRO)
- Mountings: 45° angled Surface mounted
- Diffuser options: Opal Diffuser
- Sensor: Photocell (/PC)
- IP Rating: IP65
- Housing: Polycarbonate with tamper-resistant screws.
- Dimensions: (Length x Width x Depth)
270 x 138 x 120mm

| | | | |
|---|---|--|---|
| Product | MI/ELLE 45° IP65 LED Luminaire | | |
| Light Source | LED | | |
| System Power Luminaire lumens (5000K) | /15W 1500lm | | |
| Size (Length x Width x Depth) | 270 x 138 x 120mm | | |
| Driver | /STD Non Dimming | | |
| Colour Temperature | /830 3000k | /840 4000k | |
| Colour | /BK Black | | |
| Mountings | 45° angled Surface mounted | | |
| Emergency | /ME3 Three hour maintained emergency | /ME3-ST Three hour maintained self test emergency | /ME3-PRO Three hour DALI addressable emergency |
| To Specify: ELLE LED, 15W, 1500lm, 4000k, opal diffuser LED surface mounted finished black complete with standard control gear. Part code: MI/ELLE/LED/15W/1500lm/STD/840/BK/OP | | | |

