



- A surface mounted stylish and compact circular IP65 bulkhead suitable for ceiling mount applications.

- 3W/6w LED (6W Is Non Maintained only)
- Body constructed from retardant polycarbonate
 - Powder coat finish: White (/WH)
 - Rated IP65
- Available with open area optic (/OA)

- Emergency Options:
 - Three Hour Maintained (/ME3)
 - Three Hour Non Maintained (/NME3)
 - Three Hour Non Maintained Self-Test (/NME3-ST)
 - DALI Addressable Emergency (/NME3-PRO)
- Dimensions: Diameter: Ø202mm Depth: 58mm

Product	MIS/EMLED/IP65 IP65 Standalone Emergency Luminaire			
Lamp	LED			
Lamp Power	/3W	/6W /NME3 Only.		
Installation	MIS/C/ Surface Circular			
Colour Temperature	6500k			
Colour	/WH White			
Optic Options	/OA Open Area			
Emergency	/ME3 Three hour main- tained emergency	/NME3 Three hour non-maintained emergency	/NME3-ST Three hour non-maintained self test emergency	/NME3-PRO Three hour non-maintained DALI addressable emergency
To Specify: EMLED IP65 C LED, 3W, 6500k as standard, LED surface mounted circular finished white supplied complete with three hour non maintained emergency. Part code: MIS/EMLED/IP65/C/3W/WH/OA/NME3				

