



**An economic ultra shallow LED luminaire ideally suited for open plan environments and classrooms. Panel depth of only 9mm enables installation into extremely shallow ceiling void.**

- A lumen output of 3600lm or 4100lm
- Colour Temperatures: 3000k - 4000k
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available in Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Mountings: Recessed panel as standard, Wire suspended or Surface mounted (/WS/SM)
- IP Rating: IP20 as standard, IP65 please contact technical department for further details. (/IP20/IP65)
- Dimensions for (/SM) option: (Length x Width x Depth) 600 x 605 x 50mm - with surface mounting frame (/SM)
- Refer to page 120 & 121 for ceiling system options

Product	MIR/FLT/OP Recessed Opal Diffuser LED Modular				
Light Source	LED				
System Power Luminaire lumens (4000K)	/40W 3600lm		/45W 4100lm		
Size	/55 500 x 500mm	/66 600 x 600mm	/66 600 x 600mm		
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming	/WI Wireless Control
Colour Temperature	/830 3000k		/840 4000k		
Bezel Colour	/WH White				
Diffuser Options	/OP Opal Diffuser				
Emergency	/ME3 Three hour maintained emergency	ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency	
To Specify: FLATLINE OP LED, 40W, 4000k, 3600lm LED modular recessed finished white supplied complete with DALI control gear and opal diffuser. Part code: MIR/FLT/OP/40W/3600lm/66/DALI/840/WH					

Surface mounting frame  
(/SM)



MIR/RANGE/5W/LM/SIZE/DIM/840/OPT/ME3
Style
Range abbreviation
Wattage
Lumens
Size
Driver
Colour Temperature
Options
Emergency

How to Specify