



The FLED floodlight provides a highly efficient and long-lasting alternative to HID exterior lights. Sealed to IP65 and provides a 3500k colour temperature source of light ideal for car parks, sports pitches and other exterior lighting applications.

- A rang of lumen outputs from 720-8,000lm
- Colour Temperature: 3500k
- Colour: Black as standard (/BK)
- Standard Non Dimming (/STD)
- LED sealed within impact resistant frosted polycarbonate
- Supplied complete with integral LED driver
- Stirrup bracket gives a mounting clearance of 65mm
- Available with an integral PIR sensor (/PIR)
- Rated IP65
- Die cast and extruded aluminium body
- 10W Dimensions: 110 x 140 x 46mm (L x W x D)
- 50W Dimensions: 250 x 390 x 93mm (L x W x D)
- 100W Dimensions: 370 x 460 x 131mm (L x W x D)
- Additional lumen and wattage outputs available.

Please contact technical for details

Product	MI/FLED Surface IP65 LED Luminaire		
Lamp	LED		
System Power <small>Luminaire lumens (3500K)</small>	/10W 720lm	/50W 4000lm	/100W 8000lm
Size	110 x 140 x 46mm	250 x 390 x 93mm	370 x 460 x 131mm
Driver	/STD Non Dimming		
Colour Temperature	/835 3500k		
Colour	/BK Black		/GR Grey
To Specify: FLED, 50W, 4000lm, 3500k, LED surface mounted luminaire finished black complete with standard integral control gear. Part code: MI/FLED/50W/4000lm/STD/835/BK			

