



- The FLED floodlight provides a highly efficient and long-lasting alternative to HID exterior lights. Sealed to IP65 and provides a 3500k colour temperature source of light ideal for car parks, sports pitches and other exterior lighting applications.

- Providing lumen outputs from 720-8000lm
 - Colour Temperature: 3500k
 - Die cast and extruded aluminium body
 - Rated IP65
- LED sealed within impact resistant frosted polycarbonate
 - Supplied complete with integral LED driver
- Stirrup bracket gives a mounting clearance of 65mm
 - 10W Dimensions: 110 x 140 x 46mm (L x W x D)
- 50W Dimensions: 250 x 390 x 93mm (L x W x D)
- 100W Dimensions: 370 x 460 x 131mm (L x W x D)
- Additional lumen and wattage outputs available. Please contact technical for details
- Available with an integral PIR sensor (/PIR)
- Finished black as standard

Product	MI/FLED Surface IP65 LED Luminaire		
Lamp	LED		
System Power Luminaire Lumens (3500K)	/10W 720lm	/50W 4000lm	/100W 8000lm
Size	110 x 140 x 46mm	250 x 390 x 93mm	370 x 460 x 131mm
Driver	/STD Non Dimming		
Colour Temperature	/835 3500k		
Colour	/BK Black		/GR Grey
To Specify: FLED, 50W, 4000lm, 3500k, LED surface mounted luminaire finished black supplied with complete with standard integral control gear. Part code: MI/FLED/50W/4000lm/STD/835/BK			

