




A compact fire rated IP65 LED downlight. Fitted with a faceted reflector and twist lock bezel. Tested in the UK, it has been given a fire rating of FR90 and is IP65.

- A lumen output of 773lm
- Colour Temperatures: 3000k - 4000k
- Colour: White, Black or Grey (/WH/BK/GR)
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Reflector Options: Faceted Reflector (/FR)
- FR90 and IP65 as standard
- Dimensions: (Diameter x Depth)
Ø85 x 60mm
- Cut Dimensions: (Diameter)
Ø73mm

Product	MID/FR-LED Recessed Fire Rated LED Downlight			
Light Source	LED			
System Power Luminaire lumens (4000K)	/8.1W 773lm			
Size Cutout	Ø 85mm Ø 73mm			
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming
Colour Temperature	/830 3000k		/840 4000k	
Bezel Colour	/WH White	/BK Black		/GR Grey
Reflector Options	/FR Faceted Reflector			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour main- tained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emer- gency
To Specify: FR-LED, 8.1W, 4000k, 773lm LED downlight finished white supplied with a faceted reflector. Part code: MID/FR-LED/8.1W/773lmSTD/840/WH/FR				



MIR/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3

How to Specify

Style
Range abbreviation
Wattage
Lumens
Size
Driver
Colour Temperature
Options
Emergency