



A cast aluminium LED IP65 amenity exterior luminaire available with various bezel options.

- A lumen output of 1488lm or 1951lm
- Colour Temperatures: 3000k - 4000k
- Colour: Black/ Silver/ White (/BK/GR/WH)
- Available with Dimming (/STD/DALI/SDIM)
- Wireless Control (/WI)
- Emergency Options(/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Mountings: Surface mounted
- Diffuser options: Polycarbonate opal diffuser (/OP)
- Sensor: Microwave Presence detector (/MW)
- IP Rating: IP65
- Bezel options: Hood (/HD)
- Housing: Die cast aluminium body
- Dimensions: (Length x Width x Depth) 356 x 356 x 146mm

Exterior

Product	MI/FNT Square IP65 LED Luminaire			
Light Source	LED			
System Power Luminaire lumens (4000K)	/13.6W 1488lm			/18.7W 1951m
Size	356 x 356 x 146mm			
Driver	/STD Non Dimming	/DALI DALI Dimming	/1-10V 1-10V Dimming	/MDIM Mains Dimming
Colour Temperature	/830 3000k		/840 4000k	
Colour	/BK Black	/GR Grey		/WH White
Hood Option	/HD Hood			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour main- tained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency
To Specify: FRONTIER LED, 13.6W, 1488lm, 4000k, LED surface mounted finished black supplied with standard control gear. Part code: MI/FNT/15W/1418lm/STD/840/BK/OP				

Hood Attachment (/HD)

