



## The Galaxy Version 2 is an IP65 surface mounted bulkhead emergency sign with a powder coat finish suitable for interior and exterior use.

- Colour Temperature: 4500k
- Colour: White (/WH)
- Emergency Options:
   Three Hour Maintained (/ME3),
   Three Hour Non Maintained (/NME3),
   Self Test (/ME3-ST),
   DALI Addressable Emergency (/ME3-PRO)
- Double sided legend panel as standard (/DS)
- If ME3-WI is required please speak to Technical

- Mountings: Surface as standard, semi recessing kit (/SM/SR)
- Supplied with EN7010 format legends as standard.
- IP Rating: IP65
- Self-adhesive universal legend kit for exit sign (/ULK)
- Body constructed from retardant polycarbonate
- Dimensions: (Length x Width x Depth) 350 x 120 x 65mm

GALAXY Version 2 A Ceiling Mounted Emergency Sign							
LED							
/3W 150Im (without sign exit sign)							
350 x 120 x 65mm (without exit sign)							
/STD Non Dimming			/DALI DALI Dimming				
4500k							
/WH White							
/NME3 Three hour non maintained emer- gency	/NME3 Three hour non-maintained emergency	/NME3-ST Three hour non maintained self test emergency		/NME3-PRO Three hour non DALI addressable emergency			
	/NME3 Three hour non maintained emer-	/STD Non Dimming  /NME3 Three hour non maintained emer- maintained emer- non-maintained	A Ceiling Mounted Em  LED  /3W  150lm (without sign  350 x 120 x 65 (without exit  /STD  Non Dimming  4500k  /WH  White  /NME3  Three hour non maintained emer- maintained emer- maintained mon-maintained  LED  /3W  150lm (without exit  /NHE3  Three hour non-maintained mon-maintained mon-main	A Ceiling Mounted Emergency Sign  LED  /3W  150lm (without sign exit sign)  350 x 120 x 65mm (without exit sign)  /STD Non Dimming  4500k  /WH White  /NME3 Three hour non maintained emer-non-maintained maintained self			

To Specify: GALAXY V2 LED, 3W, 4500k as standard, LED surface mounted finished white supplied complete with standard control gear, and three hour non-maintained emergency.

Part code: MI/GAL/V2/LED/3W/WH/NME3

## If exit sing is required, see our MIEX-CM V2



MIR/F	RANGI	E/5W	/LM/	SIZE.	/DIM	/840	/OPT	/ME3	
Style How to Specify	Range abbreviation	Wattage	Lumens	Size	Driver	Colour Temperature	Options	Emergency	