




Surface & Suspended

The GUIDO2 high-quality, low-glare luminaire designed for general lighting, making it ideal for classrooms and corridors.

- A range of lumen outputs from 3000-5750lm
 - Colour Temperatures: 3000K - 4000K
 - Available with Dimming (/STD/DALI/SDIM/1-10V)
 - Wireless Control (/WI)
 - Available with Emergency (/ME3/ME3-ST/ME3-PRO)
 - Wireless Emergency (/ME3-WI)
- Mountings: Surface or Wire suspended (/SM/WS)
 - Steel body with BESA fixings
 - Dimensions: (Length x Width x Height)
 - /6 - 630 x 210 x 70mm
 - /12 - 1190 x 210 x 70mm
 - /15 - 1490 x 210 x 70mm

Product	MIS/GUIDO2 Surface linear LED				
Light Source	LED				
System Power Luminaire lumens (4000K)	/25W 3000lm		/35W 4025lm		/50W 5750lm
Size	/6 630mm		/12 1190 x 210mm		/15 1490 x 210mm
Driver	/STD Non Dimming	/1-10V 1-10V Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/WI Wireless Control
Wireless Control	/WI Wireless Control				
Colour Temperature	/830 3000K			/840 4000K	
Colour	/WH White				
Diffuser Options	/OP Diffuser				
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emer- gency	
To Specify: MIS GUIDO2 LED, 1190mm, 50W, 5750lm, 4000K, surface linear finished white. Wireless Control with DALI control gear and opal diffuser. Part code: MISGUIDO2/12/50W/5750lm/DALI/WI/840/WH/OP					

Installation



MIR/RANGE/5W/LM/SIZE/DIM/840/OPT/ME3

Style	Range abbreviation	Wattage	Lumens	Size	Driver	Colour Temperature	Options	Emergency
How to Specify								