



**- A high quality, surface mounted, low glare and general purpose luminaire ideal for classrooms and corridors.**

- LED boards providing lumen outputs from 3000-6000lm
- Colour Temperatures: 3000k - 4000k
- Steel body with BESA fixings - Surface mounted or Wire suspended (/WS)
- Available with Dimming (/STD/DALI/SDIM) - Wireless Control (WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Dimensions: 630/1190/1490 x 210 x 70mm

Product	MIS/GUIDO2 Surface LED linear		
Lamp	LED		
System Power Luminaire Lumens (4000K)	/25W 3000lm	/40W 4768lm	/50W 6000lm
Size	/6 630mm	/12 1190 x 210mm	/15 1490 x 210mm
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming
Wireless Control	/WI Wireless Control		
Colour Temperature	/830 3000k		/840 4000k
Colour	/WH White		
Diffuser Options	/OP Diffuser		
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: MIS GUIDO2 LED, 1200mm, 40W, 4768lm, 4000k, surface linear finished white. Wiress Control with DALI control gear and opal diffuser. Part code: MISGUIDO2/12/40W/3768lm/DALI/WI/840/WH/OP			

