



**- A high quality, low glare and general purpose luminaire
ideal for classrooms and corridors.**

- LED boards providing lumen outputs from 3012-5760lm
 - Colour Temperatures: 3000k - 4000k
- Steel body with anti-tamper screw fixing end caps
 - Surface mounted or Wire suspended
- Available with Dimming (/STD/DALI/SDIM)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
 - Dimensions: 1175/1483 x 184 x 85mm

| | | | | |
|--|--|---|---------------------|---|
| Product | MIS/GUIDO Surface LED linear | | | |
| Lamp | LED | | | |
| Lamp Power Luminaire lumens (4000K) | /28W 3012lm | /48W 4740lm | /32W 3631lm | /52W 5760lm |
| Size | /12 1175 x 184mm | | /15 1483 x 184mm | |
| Driver | /STD Non Dimming | /DALI DALI Dimming | | /SDIM Switch Dimming |
| Colour Temperature | /830 3000k | | /840 4000k | |
| Colour | /WH White | | | |
| Diffuser Options | /RD Reeded Diffuser | | | |
| Emergency | /ME3 Three hour main- tained emergency | /ME3-ST Three hour maintained self test emergency | | /ME3-PRO Three hour DALI addressable emergency |
| To Specify: MIS GUIDO LED, 28W, 4000k, 3012lm LED surface linear finished white supplied complete with DALI control gear and opal diffuser. Part code: MISGUIDO/LED/28W/3012lm/12/DALI/840/WH/RD | | | | |

