


Flange Detail with Root

- The HAWAII is an IP66 decorative bollard with a clear inner lens and medium beam spread.
The bollard has an internal ballast tray for ease of maintenance.

- Providing lumen outputs from 1539lm
- Colour Temperature: 4000k
- Die cast and extruded aluminium body - Rated IP66
- Clear polycarbonate vandal-resistant lens, medium beam spread
- Mount kit with 200mm anchor bolts (included).
- Available as Root or Flange mounted, (Flange is required for Root Mounting option), (/RT/FL)
- Flat top, black powdercoat finish over chromate conversion coating - Sensor Option (/MW)
- Dimensions: 1095mm x Ø120mm (L x D) Head Ø260mm

Product	MI/HAWII Recessed IP67 LED Luminaire		
Lamp	LED		
System Power Luminaire Lumens (4000K)	/19.6W 1539lm		
Size	1095 x 260mm		
Driver	/STD Non Dimming		
Colour Temperature	/840 4000k		
Colour	/BK Black		
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
	To Specify: HAWAII LED, 19.6W, 1539lm, 4000k, LED bollard anchor root mounted luminaire finished black supplied with complete with standard integral control gear. Part code: MI/HAWAII/19.6W/1539lm/STD/840/BK/RT		



Exterior