




Flange Detail with Root

**The HAWAII is an IP66 decorative bollard with a clear inner lens and medium beam spread. The bollard has an internal ballast tray for ease of maintenance.**

- A lumen output of 1539lm
- Colour Temperature: 4000k
- Lens: Clear polycarbonate vandal-resistant lens, medium beam spread
- Colour: Black as standard (/BK)
- Standard Non Dimming (/STD)
- Mounting: Root or Flange mounted, (Flange is required for Root Mounting option), (/RT/FL)
- Mount kit with 200mm anchor bolts (included).
- Sensor: Microwave Sensor (/MW)
- IP Rating: IP66
- Flat top, black powder coat finish over chromate conversion coating
- Housing: Die cast aluminium body
- Dimensions: (Diameter x Height) Ø120 x 1095mm Head Ø260mm

Product	MI/HAWAII Recessed IP67 LED Luminaire		
Light Source	LED		
System Power <small>Luminaire lumens (4000K)</small>	/19.6W 1539lm		
Size	1095 x 260mm		
Driver	/STD Non Dimming		
Colour Temperature	/840 4000k		
Colour	/BK Black		
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: HAWAII LED, 19.6W, 1539lm, 4000k, LED bollard anchor root mounted luminaire finished black supplied with standard integral control gear. Part code: MI/HAWAII/19.6W/1539lm/STD/840/BK/RT			



Exterior