



- The HI-LED range is designed for use in open areas where an even uniformity is required.

Suitable for very narrow aisles, general warehousing, garages and areas where a high lumen output and shallow profile body combination is required.

- Tridonic boards providing lumen outputs from 12406-26952lm
 - 5 year system warranty for LED
 - Colour Temperatures: 3000k - 4000k
 - Available with Dimming (/STD/DALI/SDIM)
 - Available with Emergency (/ME3/ME3-ST/ME3-PRO)
 - Optional daylight sensor available (/DS)
- Surface mounted as standard
 - Available with chain suspension/ wire suspension/ drop rods/ trunking mounted (/CS/WS/DR/TM)
 - Steel body finished white
 - Opal diffuser as standard
- Dimensions: 750/1200/1750mm x 420 x 70mm

Product	MIHILED Low Bay LED		
Lamp	LED		
Lamp Power Luminaire lumens (4000K)	/95.5W 12406lm	/166.6W 21384lm	/211.5W 26952lm
Size	/07 750mm	/12 1200mm	/17 1750mm
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming
Colour Temperature	/830 3000k		/840 4000k
Colour	/WH White		
Diffuser Options	/OP Opal		
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: HILED , 95.5W, 750mm, 12406lm, 4000k, LED surface mounted finished white supplied complete with standard control gear. Part code: MIHILED/07/95.5W/12406lm/STD/840/WH/OP			

